

Highline 910 on WT - Woven textile

Product Description



| Product description | Methods | Product data |
|------------------------|------------------|--------------------|
| Construction | | |
| Structure | ISO 2424 | Tufted cut pile |
| Gauge | ISO 2424 | 1/10 |
| Pile material | DIR 96/73, 96/74 | 100% Polyamide |
| Coloration | - | Millitron |
| Backing | eTL | WT - Woven textile |
| Dimensions | CEN/TS 14159 | Approx. 400 cm |
| | ISO 3018 | Approx. 400 cm |
| Total thickness | ISO 1765 | Ca. 7,5 mm. |
| | . | 0.30" |
| Surface pile thickness | ISO 1766 | Ca. 5,0 mm. |
| Tufts | ISO 1763 | Ca. 222.000 pr.m2 |
| Total carpet weight | ISO 8543 | Ca. 2.350 g/m2 |
| | . | 69.32 oz./yd2 |
| Pile yarn weight | eTL | 910 g/m2 |
| | . | 26.85 oz./yd2 |
| Surface pile density | ISO 8543. | Ca. 0,150 g/cm3 |
| edge soil protection | eTL | Yes |

Performance ratings

| | | |
|--------------------------------|------------------------------------|-----------------------------|
| Performance areas | EN 1307 | Class 33 Commercial - Heavy |
| Wear guarantee | eTL | Contract certificate |
| Performance areas | Gulvbranchen | Klasse 33 |
| Castor chair suitability | EN 985 | Yes, constant use |
| Suitable for use on stairs | EN 1963 | Yes |
| Static control | eTL | Permanently antistatic |
| Body walking test | EN 1815 | Antistatic |
| Vertical resistance | ISO/DIS 10965 | <1x10.10 ohm |
| Acou.insu. from impact noise | EN ISO 717-2 | 28 dB |
| Acoustical absorption | eTL | 0,20 aW |
| Suitable for underfloorheating | ISO 8302 | Yes |
| Light reflectance | eTL | Testreport |
| Colour fastness to Light | ISO 105-B02 | >5 |
| | AATCC 16 | 5.0 |
| Colour fastness to rubbing wet | EN ISO 105-X12 | >3 |
| | AATCC 165 | 5.0 |
| Colour fastness to Rubbing Dry | EN ISO 105-X12 | >3-4 |
| | AATCC 165 | 5.0 |
| Colourfast. to Water Patterned | EN ISO 105-E01 | >4 |
| Cleaning | AATCC 138 | 5.0 |
| Colour fastness to Ozone | AATCC 129 | 4.5 |
| Colour fast.Oxides of Nitrogen | AATCC 164 | 4.5 |
| Other performance tests | ASTM D5252 Hexapod | 4.0/ 4.0 |
| | - | Commercial - Heavy |
| | AATCC 134 Electrostatic propensity | 3.2 kV |

Safety & Environment

| | | |
|---------------------|----------------------|---------------|
| Fire classification | DK,MK GODKENDELSE | Godkendt |
| | D,DIBT AbZ.no. | Z-156.601-441 |
| | CH,VKF/AEAI | Approved |
| | BS 6853, NF X 70-100 | Approved |

| Product description | Methods | Product data |
|---------------------|--------------------------------|-------------------|
| CE Labeling | ASTM E-648 | Class 1 |
| | ASTM E662 Smoke Density | <450 |
| | ASTM D2859 Surface Flamm. | Pass |
| | CAN,ULC-S102.2 | FSC1 86 |
| | PL, Polen std. | OK |
| | EN 13501-1 Euro Class | Cfl-s1 |
| | AU,ASISO 9239.1-2003 | 4,20 KW/m2 |
| | EN 14041 | Certified |
| | CPR | 1021-CPR-006-2/16 |
| | Declaration of Performance | DOP 1C-PA-WT |
| Indoor air | Notified body no. | 1021 |
| | Ce Year | 07 |
| | Slip resistance EN 13893 | Class DS |
| | DIM Certifikat | No.006 |
| | M1 | With WTA Backing |
| | BASTA | Registered |
| | Green Label Plus | Approved |
| | GreenLabel Singapore | Approved |
| | Emissions dans l'air intérieur | A+/A+ |
| | Environmental Choice NZ | Approved |
| Environment | GECA | Approved |
| | Byggvarudeklaration | BVD 3 |
| | BREEAM-NOR | With WTA Backing |
| | Environmental Product Decl. | EPD GUT 2009211-E |
| | Cradle To Cradle | Silver Certified |
| | LEED | Qualified |

Guides

| | | |
|------------------------------|----|----------|
| Installation+adhensive guide | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |
| Cleaning, stain removal | DK | Dansk |
| | N | Norsk |
| | S | Svensk |
| | GB | English |
| | D | Deutsch |
| | F | Francais |

Manufacturer

| | | |
|-----------------------|-----------|-------------------------------|
| Factory certification | ISO 9001 | Audited and verified by BVC |
| | ISO 14001 | Audited and verified by BVC |
| | EMAS | Audited and verified by BVC |
| | OHSAS | Audited and verified by BVC |
| | DS 49001 | Audited and verified by BVC |
| | CRuk | Member of Carpet Recycling UK |
| | TransQ | Qualified |